

RONDOFLEX(CHAIN) (N)GRDGOEU / (N)GRDGCGOEU

Low voltage cable for energy chains



Application

Applicable in all chain systems (e.g. container cranes, stacking cranes, indoor cranes, material handling equipment). Especially suitable in applications where, due to the outdoor installation, long travel distances or high travel speed, high performances are expected from the cable (such as long lifetime, full reliability, resistance to abrasion, etc.).

Global data

Brand	RONDOFLEX(CHAIN)
Type designation	(N)GRDGCGOEU-J
Type designation	(N)GRDGOEU-J/-O
Standard	Based on DIN VDE 0250-814
Certifications / Approvals	GOST-R

Design features

Conductor	Bare electrolytic copper conductor, finely stranded, class 5. Earth conductor made of bare electrolytic copper, extremely finely stranded, class FS (better than class 5).
Insulation	PROTOLON MS High grade insulation compound based on EPR (at least 3GI3); improved mechanical and electrical performance. Alternative for control cables: ETFE.
Core identification	Light colored compound with black number prints, earth yellow-green.
Core arrangement	Up to 10 ² mm: 4-core design; From 16 ² mm: 3-energy cores and splitted earth conductor into three parts.
Screen	Braid screen made of tinned copper wires. Surface covered >80%, transfer impedance <100mOhm/m at <= 30MHz
Inner sheath	Special compound based on EPR (at least GM1b); color: black
Outer sheath	High grade compound based on EVA with excellent abrasion and aging performances. Color: black.
Marking	RONDOFLEX (CHAIN) (N)GRDGOEU (number of cores)x(cross section) 0,6/1 kV

Electrical parameters

Rated voltage	0.6/1 kV (600/1000V)
Max. permissible operating voltage AC	0.7/1.2 kV
Max. permissible operating voltage DC	0.9/1.8 kV
AC Test Voltage	3.5 kV (5 Min.)
EMC	Given thanks to the special cable design
Current Carrying Capacity description	According to DIN VDE 0298, Part 4: - single cores: table 15-section 2; - multi cores: table 15-section 4.

Chemical parameters

Resistance to oil	Acc. to DIN EN 60811-404 and DIN VDE 0473-811-404, paragraph 10
Weather resistance	Unrestricted use outdoors and indoors, resistant to ozone, UV and moisture

Thermal parameters

Max. permissible temperature at conductor	90 °C
Max. short circuit temperature of the conductor	250 °C
Ambient temperature for fixed installation	min -50 °C ; max +80 °C
Ambient temperature in fully flexible operation	min -35 °C ; max +80 °C

Mechanical parameters

Max. tensile load on the conductor	15 N/mm ²
Torsional stress	Not allowed
Min. bending radius	Acc. to DIN VDE 0298 part 3
Travel speed	- In chain systems: up to 240 m/min (note: trouble free operation is influenced by several factors, among all the chain length. For long chain system we recommend to operate at lower speed).
Additional tests	Bending test, abrasion test, practical test on owned long-distance testing facility.

Number of cores x cross section	Part number	MLFB Number	Conductor diameter max. mm	Outer diameter min. mm	Outer diameter max. mm	Bending radius free moving min. mm	Weight (ca.) kg/km	Permissible tensile force max. N	Conductor resistance at 20°C max. Ω/km	Current carrying capacity (1) A	Short Circuit Current (conductor) kA
(N)GRDGOEU-O power cables, single-core design											
1x16	20003427	SDG4011	5.7	7.6	9.7	39	210	240	1.21	99	2.29
1x25	20003428	SDG4012	7.1	10.2	12.2	61	330	370	0.78	131	3.58
1x35	20168373	SDG4013	8.3	12.1	14.1	71	445	520	0.55	162	5.01
1x50	20003429	SDG4014	9.8	13.9	15.9	80	620	750	0.39	202	7.15
1x70	20003430	SDG4015	11.6	15.8	17.9	90	830	1050	0.27	250	10.01
1x95	20003431	SDG4016	13.8	19.1	21.1	106	1120	1420	0.21	301	13.59
1x120	20167027	SDG4017	14.9	20.8	22.8	114	1390	1800	0.16	352	17.16
1x150	20003432	SDG4018	17.2	23	26	130	1740	2250	0.13	404	21.45
1x185	20047699	SDG4019	18	25.2	28.2	141	2090	2770	0.11	461	26.46
1x240	20086404	SDG4020	22.5	29.9	32.9	165	2830	3600	0.08	540	34.32
(N)GRDGC OEU-O screened power cables, single-core design											
1x16C		SDG4211	5.7	10.1	12.1	61	320	240	1.21	99	2.29
1x25C		SDG4212	7.1	12.8	14.8	74	450	370	0.78	131	3.58
1x35C	20003445	SDG4213	8.3	13.7	15.7	79	540	520	0.55	162	5.01
1x50C	20003446	SDG4214	9.8	15.7	17.7	89	740	750	0.39	202	7.15
1x70C	20003447	SDG4215	11.6	18.7	20.7	104	1020	1050	0.27	250	10.01
1x95C	20003448	SDG4216	13.8	20.8	22.8	114	1260	1420	0.21	301	13.59
1x120C	20008791	SDG4217	14.9	22.8	24.8	124	1580	1800	0.16	352	17.16
1x150C		SDG4218	17.2	25.6	28.6	143	2000	2250	0.13	404	21.45
1x185C	20003449	SDG4219	18	27.7	30.7	154	2370	2770	0.11	461	26.46
1x240C		SDG4220	22.5	31.9	34.9	175	3130	3600	0.08	540	34.32
(N)GRDG OEU-J multicore power cables											
4x2,5	20025432	SDG4110	2	9.9	11.5	46	200	150	7.98	30	0.36
4x4	20003433	SDG4111	2.9	12.7	14.7	74	320	240	4.95	41	0.57
4x6	20003434	SDG4112	3.6	14.2	16.2	81	430	360	3.3	53	0.86
4x10	20003435	SDG4113	4.6	16.7	18.7	94	670	600	1.91	74	1.43
4x16	20003436	SDG4114	5.9	21.2	23.2	116	1020	960	1.21	99	2.29
4x25	20003437	SDG4115	7.2	26.5	29.5	148	1600	1500	0.78	131	3.58
3x35+3x16/3	20024514	SDG4116	8.1	26.4	29.4	147	1770	1570	0.55	162	5.01
3x50+3x25/3	20026619	SDG4117	10	31.5	34.5	173	2560	2250	0.39	202	7.15
3x70+3x35/3	20042007	SDG4119	11.9	37.6	40.6	203	3550	3150	0.27	250	10.01
5x6	20003438	SDG4122	3.6	15.8	17.8	89	530	450	3.3	53	0.86
5x10	20003439	SDG4123	4.6	19.7	21.7	109	850	750	1.91	74	1.43
5x16	20003440	SDG4124	5.9	23.4	25.4	127	1300	1200	1.21	99	2.29
(N)GRDGC OEU-J multicore power cables, overall screened											
4x2,5C	20003450	SDG4240	1.9	11.2	13.2	66	310	150	7.98	30	0.36
4x4C	20003451	SDG4241	2.9	15.2	17.2	86	490	240	4.95	41	0.57
4x6C		SDG4242	3.6	17	19	95	650	360	3.3	53	0.86
4x10C	20003452	SDG4243	4.6	19.2	21.2	106	870	600	1.91	74	1.43
3x16+3x2,5C	20003453	SDG4254	5.9	20.3	22.3	112	1050	720	1.21	99	2.29
3x25+3x4C	20003454	SDG4255	7.2	25.7	28.7	144	1610	1120	0.78	131	3.58

Number of cores x cross section	Part number	MLFB Number	Conductor diameter max. mm	Outer diameter min. mm	Outer diameter max. mm	Bending radius free moving min. mm	Weight (ca.) kg/km	Permissible tensile force max. N	Conductor resistance at 20°C max. Ω/km	Current carrying capacity (1) A	Short Circuit Current (conductor) kA
3x35+3x6C	20003455	SDG4256	8.1	28.4	31.4	157	2140	1570	0.55	162	5.01
3x50+3x25/3	20003456	SDG4257	10	34.9	37.9	190	3080	2250	0.39	202	7.15
3x70+3x35/3	20003457	SDG4258	11.8	39.8	42.8	214	4090	3150	0.27	250	10.01
3x95+3x50/3	20099906	SDG4270	13.8	43.7	46.7	234	5080	4270	0.21	301	13.59
5x16C	20003459	SDG4264	5.9	25.7	28.7	144	1630	1200	1.21	99	2.29
(N)GRDGOEU-J control cables											
12x1,5	20154051	SDG4152	1.5	11.7	13.7	69	305	270	13.3	23	0.21
24x1,5	20003441	SDG4154	1.5	19.9	21.9	110	710	540	13.3	23	0.21
7x2,5		SDG4141	1.9	11.3	13.3	67	290	260	7.98	30	0.36
12x2,5	20003442	SDG4190	1.9	15.3	17.4	87	490	450	7.98	30	0.36
18x2,5	20003443	SDG4191	1.9	19.5	21.5	108	760	670	7.98	30	0.36
24x2,5	20003444	SDG4192	1.9	22.5	24.5	123	1020	900	7.98	30	0.36
(N)GRDGOEU-J overall screened control cables											
12x1,5C	20007106	SDG4252	1.5	14.6	16.6	83	490	180	7.98	23	0.36
5x2,5C	20007107	SDG4260	1.9	12.7	14.7	74	435	270	13.3	30	0.21
(N)GRDGOEU-O bus cables											
1x(2x0,5)C		SDG4***	0.9	8	10	40	135	10	39	10	0.07
(4x2x0,5)C	20007108	SDG4279	0.9	17.6	19.6	98	500	60	39	10	0.07
4x(2x0,5)C	20003460	SDG4280	0.9	19	21	105	590	60	39	10	0.07
6x(2x0,5)C	20003461	SDG4281	0.9	22.2	24.2	121	820	90	39	10	0.07
6x(2x1)C	20003458	SDG4259	1.3	26.3	29.3	147	1130	180	19.5	18	0.14
Fiber Optic											
6G62,5/125μ	20003462	SDG4290		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
12G62,5/125μ	20003463	SDG4291		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
6E9/125μ	20003464	SDG4292		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
18G50/125μ	20003465	SDG4293		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
12G50/125μ	20003466	SDG4294		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
18G62,5/125μ	20024515	SDG4295		12.6	14.6	73	250	500	n.a.	n.a.	n.a.
6G50/125μ	20060691	SDG4296		12.6	14.6	73	250	500	n.a.	n.a.	n.a.

(1) Nominal current carrying capacity for rubber cables laid on a surface, at 30°C ambient temperature (see also VDE 0298-4, Table 15).

NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.